




X600 PRO FULLY RUGGED NOTEBOOK

- 11세대 Intel® Core™ i9 / i7 / i5 vPro® Processor
- 15.6" FHD LumiBond® display with Getac sunlight readable technology (1,000 nits) and capacitive touchscreen (옵션)
- Enhanced enterprise security features with TPM 2.0, Kensington lock, triple user-replaceable storage and Smart card reader
- Versatile I/Os connectivity including Thunderbolt™ 4 and docking solutions
- Discrete graphic NVIDIA® Quadro® RTX3000 (옵션)
- Expandable modules for additional ports, batteries, DVD super multi drive, and connectivity



X600 Pro 3D demo



SPECIFICATIONS

운영체제
Windows 11 Pro

CPU
Intel® Core™ i5-11500H vPro® Processor
Max. 4.6GHz with Intel® Turbo Boost Technology
- 12MB Intel® Smart Cache

Platform options:
Intel® Core™ i7-11850H vPro® Processor
Max. 4.8GHz with Intel® Turbo Boost Technology
- 24MB Intel® Smart Cache

Intel® Core™ i9-11950H vPro® Processor
Max. 4.9GHz with Intel® Turbo Boost Technology
- 24MB Intel® Smart Cache

그래픽 컨트롤러
Intel® UHD Graphics
옵션: NVIDIA® Quadro® RTX3000 6GB discrete graphics controller^{i, ii, iii}
옵션: NVIDIA® GeForce® GTX1650 4GB discrete graphics controller^{i, ii}

디스플레이
15.6" TFT LCD FHD (1920 x 1080) Protection film
1,000 nits LumiBond® display with Getac sunlight readable technology
옵션: Capacitive multi-touch screen

스토리지 & 메모리
16GB DDR4
옵션: 32GB / 64GB / 128GB DDR4
512GB PCIe SSD
옵션: 1TB / 2TB PCIe SSD
옵션 2nd storage: 512GB / 1TB / 2TB PCIe SSD
옵션 3rd storage: 512GB / 1TB / 2TB PCIe SSD

키보드
LED backlit membrane keyboard with integrated numeric keypad

포인팅 장치
Touchscreen
- 옵션: Capacitive multi-touch screen
Touchpad
- Touchpad with two buttons

확장 슬롯
Smart card reader
ExpressCard 54 + PCMCIA Type II
옵션: 2nd ExpressCard 54 or 2nd PCMCIA Type II^{iv}
옵션: SD card reader

Multimedia Bay
Multimedia bay battery (11.1V, typical 4200mAh; min. 3980mAh)
DVD super multi drive^v
옵션: Multimedia bay 2nd battery (11.1V, typical 4200mAh; min. 3980mAh) or Blu-Ray super multi drive^v

	Office Dock	Vehicle Dock
Serial Port	1	1
External VGA	1	1
Microphone	1	-
Audio Output	1	-
DC in Jack	1	1
USB	5	6
LAN	2	2
HDMI	1	1
Display port	1	1
RF Antenna Connector	-	1 (GPS, WWAN, WLAN)
Kensington lock	1	1

I/O 인터페이스
FHD webcam x 1
Thunderbolt™ 4 Type C x 1
USB 3.2 Gen 2 Type-A x 4
LAN (RJ-45) x 2
Audio in/out combo x 1
DC in Jack x 1
HDMI 2.0 x 1
Display port x 1
Docking connector x 1
Serial port (9-pin; D-sub) x 2
External VGA (15-pin; D-sub) x 1 or 3rd Serial port (9-pin; D-sub) x 1^{vi}
옵션: SIM card slot x 1 (Mini-SIM, 2FF)^{vii}
옵션: RF antenna pass-through for GPS, WWAN and WLAN x 1

통신 인터페이스
2.5GBASE-T Ethernet
Intel® Wi-Fi 6E AX210, 802.11ax
Bluetooth (v5.2)^{viii}
옵션: Dedicated GPS^{ix}
옵션: 4G LTE mobile broadband with integrated GPS^{vii, ix}

보안 기능
TPM 2.0
Kensington lock
Smart card reader
Intel® vPro® Technology

전원
AC adapter (230W, 100-240VAC, 50/60Hz)ⁱ
Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2
Multimedia bay battery (11.1V, typical 4200mAh; min. 3980mAh) x 1
옵션: Multimedia bay 2nd battery (11.1V, typical 4200mAh; min. 3980mAh)^v

치수 & 무게
412 x 322 x 77.4mm (16.22" x 12.68" x 3.05")^x
6.05kg (13.34lbs)^x

경고성
MIL-STD-810H certified
IP66 certified
MIL-STD-461G certified^{xi}
Vibration and 4ft (1.2m) drop resistant
옵션: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D)
옵션: Salt fog certified

사용가능 환경
Temperature^{xii}:
- Operating: -29 C to 63°C / -20°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

소프트웨어
Getac Utility
Getac Geolocation
옵션: Absolute Persistence®

X600 PRO FULLY RUGGED NOTEBOOK

악세서리
Battery (10.8V, typical 6900mAh; min. 6600mAh) x 2
Multimedia bay battery (11.1V, typical 4200mAh; min. 3980mAh) x 1
AC adapter (230W, 100-240VAC, 50/60Hz)ⁱ
Capacitive stylus with tether

옵션:
Backpack
Battery (10.8V, typical 6900mAh; min. 6600mAh)
Multimedia bay battery (11.1V, typical 4200mAh; min. 3980mAh)
Multi-Bay charger (Dual-Bay)
Multimedia bay DVD super multi drive^v
Multimedia bay Blu-Ray super multi drive^v
AC adapter (230W, 100-240VAC, 50/60Hz)ⁱ
Office dock AC adapter (230W, 100-240VAC, 50/60Hz)ⁱ
MIL-STD-461 AC adapter (230W, 100-240VAC)^{xi}
DC-DC vehicle adapter (230W, 11-32VDC)
Capacitive stylus with tether
Protection film
Vehicle dock
Office dock
Spare SSD kit

I. The configuration with a discrete graphic controller requires the 230W AC adapter.
II. 150W AC adaptor is not applicable with discrete graphic controller nor office dock.
III. For X600 Pro optional NVIDIA® Quadro® RTX3000, the operating temperature is 0°C to 63°C / 32°F to 145°F.
IV. The 2nd ExpressCard 54 and the 2nd PCMCIA Type II card readers are mutually exclusive.
V. DVD super multi drive, Blu-Ray super multi drive, and the 2nd multimedia bay battery are mutually exclusive.
VI. The 3rd Serial port is optional and mutually exclusive with External VGA.
VII. Units with 4G LTE option comes with an embedded SIM card slot.
VIII. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
IX. Dedicated GPS and 4G LTE are mutually exclusive options.
X. Weight and dimensions vary from configurations and optional accessories.
XI. MIL-STD-461 230W AC adapter sold separately.
XII. Tested by an independent third-party test lab following MIL-STD-810H.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

